

# S P E C I F I C A T I O N S

BRAND / MODEL	KIA CARENS		
	LX M/T	LX A/T	EX A/T
<b>DIMENSIONS</b>			
OVERALL LENGTH (mm)	4,545		
OVERALL WIDTH (mm)	1,800		
OVERALL HEIGHT (mm)	1,650		
WHEELBASE (mm)	2,700		
FRONT TREAD (mm)	1,575		
REAR TREAD (mm)	1,570		
GROUND CLEARANCE (mm)	156		
CURB WEIGHT (kg)	1,581	1,597	
GROSS VEHICLE WEIGHT (kg)	2,135	2,155	
MINIMUM TURNING RADIUS (m)	5.3		
<b>ENGINE</b>			
DESCRIPTION)	2.0 Gasoline, DOHC, 16 Valves, CVVT (Continuous Variable Valve Timing) with Catalytic Converter		
DISPLACEMENT (cc)	1,998		
BORE X STROKE (mm)	86.0 x 86.0		
MAXIMUM OUTPUT (ps/rpm)	145 @ 6,000		
MAXIMUM TORQUE (kg-m/rpm)	19.2 @ 4,250		
FUEL TANK CAPACITY (L)	55		
<b>DRIVETRAIN / CHASSIS</b>			
STEERING	Power Rack and Pinion		
DRIVETRAIN	Front Wheel Drive		
TRANSMISSION	5-Speed Manual	4-Speed AT with Neuro Fuzzy AT System	
BRAKES (front)	8" Ventilated Disc		
BRAKES (rear)	9" Solid Disc		
SUSPENSION (front)	MacPherson Strut Type with Stabilizer Bar		
SUSPENSION (rear)	Multi Link with coil spring and stabilizer bar		
WHEEL SIZE	15 x 6.0 J (Steel with cover)	15 x 6.0 J (Alloy)	
TIRE SIZE	205 / 65 R15		
<b>SAFETY</b>			
AIRBAGS	—	—	Driver Side
SEAT BELTS (front)	Height Adjustable 3 pt. ELR x 2		
2nd row	3 pt. ELR x 2 + Lapbelt		
3rd row	3 pt. ELR x 2 + Lapbelt		
HIGH MOUNTED STOP LAMP	Std.		
FOGLAMPS	—	—	Std.
REAR WINDSHIELD	with Defogger, wiper, and washer		
IMPACT ABSORBING BODY	Std.		
SIDE IMPACT BEAMS	Std.		