



With the new 12-seater, the interior has been configured to ensure spacious seating for twelve people. This way, you get generous leg room and moving area so you can stretch out comfortably when going places.


2.7-liter DIESEL ENGINE
Delivers extra power for excellent high-speed cruising and acceleration.



RECLINABLE SEATS WITH ADJUSTABLE HEADRESTS
Puts the body in the most restful position for optimum riding posture for both the driver and passengers.



AMPLE CARGO SPACE
Foldable backseats make loading space possible in an instant.



COMFORT

- Power-steering with steering lock
- Rear door auto lock
- Reclining front seats with detachable headrests
- Non-CFC dual airconditioning
- 4-speaker AM/FM stereo system
- Fully-reclining rear seats with headrests
- Cupholders
- Rear assist grips
- Accessories pouch

DEPENDABILITY

- 2.7 -liter diesel engine
- Independent double wishbone torsion bar-type with telescopic shock absorber front suspension
- Semi-elliptic leaf springs with telescopic shock absorber rear suspension

SAFETY

- Front and rear seatbelts
- Ventilated front disc brakes
- Rear leading-trailing type drum brakes with automatic brake adjuster
- Halogen headlamps
- Load Sensing Valve
- Rear underview mirror
- Rear door glass wiper
- Rear door glass defogger

STYLE

- 2-tone body color
- Color-keyed bumpers
- Rear bumper with step
- 2-tone seat upholstery
- Side stripes
- Re-designed chrome grill
- Vinyl with fabric door trim

DIMENSION, WEIGHT & PERFORMANCE

Model		Microbus	
		Long Body	
		Standard Roof	
		4 Door	
		VX 12 - passenger	
Overall Length	mm	4990	
Overall Width	mm	1690	
Overall Height	mm	1990	
Wheelbase	mm	2715	
Tread	Front	mm	1470
	Rear	mm	1450
Min. Road Clearance	mm	186	
Cargo or Passenger Room	Length	mm	3035
	Width	mm	1510
	Height	mm	1325
Gross Vehicle Weight	kg	3100	
Curb Weight*	kg	1945	
Minimum Turning Radius	mm	5.4	
Fuel Tank Capacity	L	65	
Tires		195R15C-8PR	
Wheels		15 x 5 1/2 JJ 45	
Engine Type		ZD30DD	

Mechanical Features

Model		ZD30DD
Engine	Type	Diesel, 4-cyl. In-line, DOHC
	Bore x Stroke	mm 96.0 x 102.0
	Displacement	cc 2953
	Max. Power	kW(PS)/rpm(ECC) 77(105)/3800
	Max. Torque	Nm(kg-m)/rpm(EEC) 209(21.3)/2000
	Compression Ratio	18.5 to 1
Fuel System		ECCS, electronic fuel injection control
Transmission Gear Ratio	Type	Manual 5-speed
	1st	3.592
	2nd	2.246
	3rd	1.415
	4th	1.000
	5th	0.0821
	Rev	3.657
Final Gear Ratio (hyphoid final gear)		4.875 (4.900) *1
Steering		Rack-and-pinion with power assist
Suspension	Front	Independent double-wishbone torsion bar type with telescopic shock absorbers / Stabilizer
	Rear	Rigid axle semi-elliptic leaf springs with telescopic shock absorbers
Brakes	Front	15 - inch ventilated discs
	Rear	Drums / Automatic brake adjuster
	Control Valve	LSV (Load-Sensing Valve)