

	2.5 DSL M/T
Engine	
Model	2KD-FTV
Engine Technology	Direct Injection Four-Stroke Common-Rail Diesel (D-4D)
Type	2.5 Liter Diesel, 4-Cylinder, In-line 16V, Double Overhead Camshaft (Turbo Charged)
Displacement	2494
Maximum Output PS/Rpm	102/3600
Maximum Torque Nm/Rpm	A/T:260/1600-2400
Bore and Stroke	92.0x93.8
Compression Ratio	18.5:1
Fuel System	Direct Injection Common-Rail
	2.5 DSL M/T
Dimensions & Weight	
Overall L x W x H	4555 x 1770 x 1755
Wheelbase	2750
Tread Front/Rear	1510
Min. Turning Radius	5.4
Fuel Tank Capacity	55
Seating Capacity	8
Curb Weight	1605
	2.5 DSL M/T
Transmission and Chassis	
Transmission Type	5-Speed Manual
Suspension Front/Rear	Independent, Coil Spring, Double Wishbone w/ Stabilizer Bar / 4-Link, Coil Spring
Brakes Front/Rear	Ventilated Discs / Leading-Trailing Drum
Steering System	Rack and Pinion with Power Steering
Tires and Wheels	205/65R156JJx15", Alloy with Center Cap